

MATERIAL SAFETY DATA SHEET

Section 1: Product & Company Identification

Product Name: Ultra-Lite 3-36®

Product Number (s): 03160, 83160

Manufactured By: CRC Industries, Inc. (215) 674-4300
885 Louis Drive, Warminster, PA 18974
24-Hour Emergency Information: CHEMTREC (800) 424-9300

Section 2: Composition/Information on Ingredients

Component	CAS NUMBER	ACGIH TLV	OSHA PEL	OTHER LIMITS	%
Petroleum Distillate	64742-47-8	NE	500 ppm	NE	80-90
Paraffin Wax	8002-74-2	NE	NE	NE	<10
Carbon Dioxide	124-38-9	5000 ppm	10000 ppm	NE	3-6

Section 3: Hazards Identification

Emergency Overview

Appearance & Odor: Amber liquid, petroleum distillate odor.

DANGER: Flammable. Harmful or fatal if Swallowed. Contents Under Pressure.

Potential Health Effects:

Inhalation: Headaches, dizziness, nausea and breathing problems.

Eyes: Irritation

Skin: Irritation

Ingestion: May cause throat irritation, nausea, vomiting and diarrhea. Aspiration into lungs may cause lung injury and possible death.

Carcinogenicity: OSHA: No IARC: No NTP: No
Chronic Overexposure: Dermatitis
Medical Conditions Aggravated by Exposure: NA

Section 4: First Aid Measures

Inhalation: Remove to fresh air. Give artificial respiration if necessary.

Eyes: Flush with large amounts of water for 15 minutes.

Skin: Remove contaminated clothing and wash area with soap and water.

Ingestion: Call a physician. Do not induce vomiting.

Section 5: Fire-Fighting Measures

Flashpoint:	160°F	Method:	TCC	LEL:	ND	UEL:	ND
Extinguishing Media:	CO ₂ , dry chemical and foam						
Hazardous Combustion Products:	CO ₂ , Carbon monoxide (fire)						
Fire-fighting Instructions:	Remove containers from fire area if possible. Use self-contained breathing apparatus for fire fighting. Aerosol cans may explode if heated above 120°F.						
NFPA:	Health:	1	Flammability:	2	Reactivity:	0	
HMIS:	Health:	1	Flammability:	2	Reactivity:	0	PPE: B

Section 6: Accidental Release Measures

Spill/Leak Procedures: Usually not a problem with aerosols. Area should be ventilated. Absorbent should be used to pick up excess material. All used and unused product should be disposed of in accordance with federal, state and local regulations.

Section 7: Handling and Storage

Handling Procedures: Use with adequate ventilation. Wash hands after using.

Storage Procedures: Store in a cool, dry area. Aerosol cans must be maintained below 120°F to prevent cans from exploding. Keep out of reach of children!

Section 8: Exposure Controls/Personal Protection

Engineering Controls: Adequate to prevent accumulation of vapors. Use mechanical means if necessary to maintain levels below the exposure limits. If working in a confined space, follow applicable OSHA regulations.

Respiratory: Use NIOSH/MSHA compliant respirators or self-contained breathing apparatus above exposure limits. Follow OSHA regulations 29 CFR 1910.134.

Protective Clothing/Equipment: Wear chemically protective gloves and safety glasses. Use a splash apron and boots if splashing occurs.

Section 9: Physical & Chemical Properties

Physical State:	Liquid	Appearance & Odor:	Amber liquid, petroleum distillate odor.
Specific Gravity:	0.8043	Boiling Point:	385°F
Freezing Point:	ND	Vapor Pressure:	< 1 mm
Evaporation Rate:	slow .01 (toluene=1)	Vapor Density (air = 1)	> air 4.5
pH:	NA	Solubility:	Insoluble in water. Soluble in hydrocarbon solvents.
Volatile Organic Compounds %:	87.3	g/L:	701
		lbs./gal:	5.85

Section 10: Stability and Reactivity

Stability:	Stable	Hazardous Polymerization:	No
Chemical Incompatibilities:	Strong oxidizers.		

Conditions to Avoid: Temperature extremes.
Hazardous Decomposition Products: None

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. See Section 3 of this MSDS for acute symptoms of overexposure and carcinogenicity information.

Section 12: Ecological Information

Ecotoxicity: No data available.
Environmental Fate: No data available for biodegradation.

Section 13: Disposal Considerations

Disposal: This material if discarded may be hazardous waste under U.S. EPA RCRA regulations. All disposal activities must comply with federal, state and local regulations. Contact your local or state environmental agency for specific rules. Do not dump into sewers, on the ground or into any body of water.

Section 14: Transportation Information

Shipping Name: Consumer Commodity
Hazard Class: ORM-D UN Number: NA Packing Group: NA
Label: NA Placard: NA
Special Provisions: NA

Section 15: Regulatory Information

TSCA: All components are either listed under TSCA or are exempt.
SARA Title III: Section 311/312: Acute, Pressure Section 313*: None
CERCLA/Superfund (RQ): NA
Extremely Hazardous Substances: No
California Prop 65: No
New Jersey Right to Know: Polyolester (#800967-5543) : 5%

* See section 2 for percentage

Section 16: Additional Information

Prepared By: Michelle Milburn Date: January 2, 2004
Technical Information: (800) 521-3168 CRC #: 559
This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS:	Chemical Abstract Service	NA:	Not Applicable
ppm:	Parts per Million	ND:	Not Determined
TCC:	Tag Closed Cup	NE:	Not Established
LEL:	Lower Explosive Limit	g/L:	grams per Liter
UEL:	Upper Explosive Limit	lbs./gal:	pounds per gallon
PPE:	Personal Protection Equipment	RQ:	Reportable Quantity