

Version 2.0

### Revision Date 03/06/2017

Print Date 05/02/2017

Zepinc

#### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	:	A00264AM MST ALPINE MIST XD TRF 12n5		
Material number	:	0000000001039402		
Manufacturer or supplier's details				
Company	:	Zep Inc.		
Address	:	1310 Seaboard Industrial Blvd., NW Atlanta, GA 30318		
Telephone	:	404-352-1680		

### Emergency telephone numbers

For SDS Information	:	Compliance Services 1-877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation	:	CHEMTREC: 800-424-9300 - All Calls Recorded.
Emergency		In the District of Columbia 202-483-7616

### Recommended use of the chemical and restrictions on use

Recommended use : Air Care

#### SECTION 2. HAZARDS IDENTIFICATION

#### **Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	colourless
Odour	odourized

#### **GHS Classification**

Flammable aerosols	:	Category 2
Gases under pressure	:	Liquefied gas
Eye irritation	:	Category 2A
Specific target organ toxicity -	:	Category 3 (Central nervous system)
single exposure		

#### **GHS** label elements

Hazard pictograms	
Signal word	: Warning
Hazard statements	<ul> <li>H223 Flammable aerosol.</li> <li>H280 Contains gas under pressure; may explode if heated.</li> <li>H319 Causes serious eye irritation.</li> <li>H336 May cause drowsiness or dizziness.</li> </ul>
Precautionary statements	: <b>Prevention:</b> P210 Keep away from heat/sparks/open flames/hot surfaces.



# AND 264 AM MOT AL DINE MIGT YD TDE 1205

Version 2.0	Revision Date 03/06/2017	Print Date 05/02/2017
	No smoking.	
	P211 Do not spray on an open fla	ame or other ignition source.
	P251 Pressurized container: Do use.	÷
	P261 Avoid breathing dust/ fume	/ gas/ mist/ vapours/ spray.
	P264 Wash skin thoroughly after	• • • • •
	P271 Use only outdoors or in a v	vell-ventilated area.
	P280 Wear eye protection/ face	protection.
	Response:	
	P304 + P340 + P312 IF INHALEE and keep comfortable for breathin	ng. Call a POISON
	CENTER/doctor if you feel unwel	
	P305 + P351 + P338 IF IN EYES for several minutes. Remove con easy to do. Continue rinsing.	
	P337 + P313 If eye irritation pers	ists: Get medical advice/
	attention.	
	Storage:	
	P410 + P412 Protect from sunlig	ht. Do not expose to
	temperatures exceeding 50 °C/ 1	
	P403 Store in a well-ventilated pl	
	Disposal:	
	Dispose of contents/container in regulation.	accordance with local

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Hazardous components

CAS-No.	Concentration [%]
67-64-1	>= 70 - < 90
74-98-6	>= 10 - < 20
106-97-8	>= 5 - < 10
_	67-64-1 74-98-6

The exact percentages of disclosed substances are withheld as trade secrets.

#### **SECTION 4. FIRST AID MEASURES**

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Consult a physician after significant exposure. If unconscious place in recovery position and seek medical advice.
In case of skin contact	<ul> <li>Wash off immediately with plenty of water for at least 15 minutes.</li> <li>Remove contaminated clothing and shoes.</li> <li>Wash contaminated clothing before reuse.</li> <li>If skin irritation persists, call a physician.</li> </ul>
In case of eye contact	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.



Version 2.0	Revision Date 03/06/2017	Print Date 05/02/2017
	Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a s	pecialist.
If swallowed	<ul> <li>Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.</li> <li>DO NOT induce vomiting unless directed to do so by a physician or poison control center.</li> </ul>	
Most important symptoms and effects, both acute and delayed	<ul> <li>Effects are dependent on exposure (dose, concentration, contact time).</li> <li>Effects are immediate and delayed.</li> <li>Symptoms may include irritation, redness, pain, and rash.</li> <li>Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness.</li> <li>Causes serious eye irritation.</li> <li>May cause drowsiness or dizziness.</li> <li>Review section 2 of SDS to see all potential hazards.</li> </ul>	
Notes to physician	: Treat symptomatically. Symptoms	may be delayed.

#### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	cohol-resistant foam ırbon dioxide (CO2) y chemical	
Unsuitable extinguishing media	gh volume water jet	
Specific hazards during firefighting	o not allow run-off from fire fig urses.	nting to enter drains or water
Hazardous combustion products	rbon dioxide (CO2) rbon monoxide noke	
Specific extinguishing methods	e extinguishing measures that cumstances and the surround	
Further information	r safety reasons in case of fin parately in closed containmer e a water spray to cool fully of e residues and contaminated disposed of in accordance w	nts. closed containers. fire extinguishing water must
Special protective equipment for firefighters	ear self-contained breathing a cessary.	apparatus for firefighting if

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal	precautions,
----------	--------------

: Use personal protective equipment.



Version 2.0	Revision Date 03/06/2017	Print Date 05/02/2017
protective equipment and emergency procedures	Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to concentrations. Vapours can accum	
Environmental precautions	: Prevent product from entering drains Prevent further leakage or spillage in If the product contaminates rivers ar respective authorities.	safe to do so.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent materia acid binder, universal binder, sawdu Sweep up or vacuum up spillage and container for disposal.	st).

## SECTION 7. HANDLING AND STORAGE

Advice on safe handling	<ul> <li>Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Always replace cap after use. Dispose of rinse water in accordance with local and national regulations. Do not breathe vapours or spray mist.</li> </ul>
Conditions for safe storage	<ul> <li>BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking.</li> <li>Observe label precautions.</li> <li>Electrical installations / working materials must comply with the technological safety standards.</li> <li>Keep in a dry, cool and well-ventilated place.</li> </ul>
Materials to avoid	: Oxidizing agents Store and keep away from bases and alkalies.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	
		exposure)	Permissible	
			concentration	
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm	NIOSH REL



Version 2.0 Revision Date 03/06/2017 Print Date 05/02/2017

			590 mg/m3	
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
		STEL	750 ppm 1,780 mg/m3	CAL PEL
		С	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL

#### **Biological occupational exposure limits**

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

#### **Engineering measures**

: effective ventilation in all processing areas

### Personal protective equipment

 Respiratory protection
 : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

 Hand protection
 .

 Material
 : Protective gloves

 Remarks
 : The suitability for a specific workplace should be discussed

Romano	•	with the producers of the protective gloves.
Eye protection	:	Safety glasses Ensure that eyewash stations and safety showers are close to

the workstation location.



Version 2.0	Revision Date 03/06/2017	Print Date 05/02/2017	
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work pla		
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at	the end of workday.	

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Colour	: colourless
Odour	: odourized
Odour Threshold	: No data available
рН	: Not applicable
Melting point/freezing point	: No data available
Boiling point	: No data available
Flash point	:
	Not applicable
Evaporation rate	: No data available
Flammability (solid, gas)	: Flammable aerosol.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: <1 g/cm3
Bulk density	: No data available
Solubility(ies)	
Water solubility	: soluble
Solubility in other solvents	: soluble
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Heat of combustion	: 34.89 kJ/g

Version 2.0

Revision Date 03/06/2017



Print Date 05/02/2017

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Bases Oxidizing agents Amines
Hazardous decomposition products	: Carbon monoxide Carbon dioxide (CO2)

#### SECTION 11. TOXICOLOGICAL INFORMATION

#### **Potential Health Effects**

Aggravated Medical Condition Symptoms of Overexposure	<ul> <li>None known.</li> <li>Effects are dependent on exposure (dose, concentration, contact time).</li> <li>Effects are immediate and delayed.</li> <li>Symptoms may include irritation, redness, pain, and rash.</li> <li>Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness.</li> </ul>
Carcinogenicity:	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

## Acute toxicity

Components:

## SAFETY DATA SHEET



Version 2.0	Revision Date 03/06/2017	Print Date 05/02/2017
acetone:		
Acute oral toxicity	: LD50 Rat: 5,800 mg/kg	
Acute inhalation toxicity	: LC50 Rat: 132 mg/l Exposure time: 3 h	
	LC50 Rat: 50.1 mg/l	
Acute dermal toxicity	: LD50 Guinea pig: > 7,426 mg/kg	
	LD50 Rabbit: > 7,426 mg/kg	
<b>propane:</b> Acute inhalation toxicity	: LC50 Mouse: 1,237 mg/l Exposure time: 2 h	
	LC50 Rat: 658 mg/l Exposure time: 4 h	
	LC50 Rat: 1,355 mg/l	
<b>butane:</b> Acute inhalation toxicity	: LC50 Mouse: 1,237 mg/l Exposure time: 2 h	
	LC50 Rat: 1,355 mg/l	
Skin corrosion/irritation		
Product:		
Remarks: May cause skin irrit	ation in susceptible persons.	
Serious eye damage/eye irritatio	on	
Product:		
Remarks: Severe eye irritation	n	
Respiratory or skin sensitisation		
No data available		
Germ cell mutagenicity		
No data available		
Carcinogenicity		
No data available		
Reproductive toxicity		
No data available		
acetone: propane:		

ZepInc



Version 2.0

Revision Date 03/06/2017



Print Date 05/02/2017

#### butane:

#### STOT - single exposure

No data available

### STOT - repeated exposure

No data available

#### Aspiration toxicity

No data available

#### **Further information**

#### Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

No data available

#### Persistence and degradability

No data available Bioaccumulative potential

#### Product:

Partition coefficient: n- octanol/water <u>Components:</u> butane :	: Remarks: No data available
Partition coefficient: n- octanol/water	: Pow: 2.89
Mobility in soil	
No data available	
Other adverse effects	
No data available Product:	
Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological	: No data available



Version 2.0

Revision Date 03/06/2017

information

#### SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	<ul> <li>Do not dispose of waste into sewer.</li> <li>Do not contaminate ponds, waterways or ditches with chemical or used container.</li> <li>Dispose of in accordance with local regulations.</li> </ul>
Contaminated packaging	<ul> <li>Empty remaining contents.</li> <li>Dispose of as unused product.</li> <li>Do not re-use empty containers.</li> <li>Do not burn, or use a cutting torch on, the empty drum.</li> </ul>

#### SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): This material is not classified.

Transportation Regulation: IMDG (Vessel): This material is not classified.

Transportation Regulation: IATA (Cargo Air): This material is not classified.

Transportation Regulation: IATA (Passenger Air): This material is not classified.

Transportation Regulation: TDG (Canada): This material is not classified.

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

#### SECTION 15. REGULATORY INFORMATION

TSCA list

: No substances are subject to a Significant New Use Rule. No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

#### CERCLA Reportable Quantity



Version 2.0

Revision Date 03/06/2017

Print Date 05/02/2017

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

## SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	: Sudden Release of Pressure Hazard Acute Health Hazard Fire Hazard					
SARA 302	: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.					
SARA 313	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.					
California Prop 65	This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.					
The components of this product are reported in the following inventories:						
	On TSCA Inventory All components of this product are on the Canadian DSL					
For information on the country notification status for other regions please contact the manufacturer's regulatory group.						
Inventory Acronym and Validity Area Legend:						

TSCA (USA), DSL (Canada), NDSL (Canada)


### SECTION 16. OTHER INFORMATION



Version 2.0

Revision Date 03/06/2017





#### **OSHA - GHS Label Information:**

Hazard pictograms	
Signal w ord	: Warning:
Hazard statements	<ul> <li>Flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness.</li> </ul>
Precautionary statements	: Prevention: Keep aw ay from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/ vapours/spray. Wash skin thoroughly after handling. Use only outdoors or in a w ell-ventilated area. Wear eye protection/face protection. <b>Response:</b> IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unw ell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention. <b>Storage:</b> Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a w ell-ventilated place. <b>Disposal:</b> Dispose of contents/container in accordance with local regulation.

Version:	2.0
Revision Date:	03/06/2017
Print Date:	05/02/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical<sup>™</sup>, Selig<sup>™</sup>, Misty®, Next Dimension<sup>™</sup>, Petro®, i-Chem®, TimeMist®, TimeWick<sup>™</sup>, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National<sup>™</sup>, FC Forward Chemicals®,Rexodan®, Mykal<sup>™</sup>, and a number of private labeled brands.



Version 2.0

Revision Date 03/06/2017

Print Date 05/02/2017