MATERIAL SAFETY DATA SHEET CLOVER TECHNOLOGIES									
MAY BE USED TO COMPLY WITH OSHA'S			4200 COLUMBUS STREET			elite [®]			
INCARD COMMONICATION STAINDARD OTTAWA, ILLINOIS 01550									
29CRF 1910.1200 EMERGENCY TELEPHONE NUMBER 1-800-464-0272									
INFORMATION TELEPHONE NUMBER 1-800-464-0272									
	DATE PREP	PARED: 11/1/13			REPARER (OPTIONAL)				
SECTION 1 CH									
SECTION 1 CHEMICAL PRODUCT / NAME Product/Chemical Name: Toner for use in Brother TN720/750/780 Cartridge									
oduct No: CAS	ELI75900								
Number: Other	Mix	ture							
Designations:	N/A	L.							
General Use:	Las	er Printer							
SECTION 2 CO	MPOSITION	/ INFORMATION	ON INGREDIE	INTS					
		CAS	EU	%	OSHA	ACGIH	REACH		
Ingredient Name:	:	NUMBER	NUMBER	70	PEL	TLV	REGISTRATIO		
Sturana Asnulata C		Confidential		70.90	Not listed	Not listed	Dra Dagistarad		
Styrene-Acrylate C	opolymei	Confidential		70-80	Not listed	NULIISLEU	Pre- Registered		
Wax		Confidential		2 - 8	Not listed	Not listed	Pre- Registered		
							Ũ		
Carbon Black		1333-86-4		2 - 8	3.5mg/m ³	3.5mg/m ³	Pre- Registered		
						2 °			
Silica		Confidential		1 - 6	Not listed	10mg/m ³	Pre- Registered		
Melamine Resin		Confidential		1 - 3	Not listed	10mg/m ³	Pre- Registered		
* Total dust for res	pirable part,	3.5mg/m3		Tone	er is regulated under OS		ite not		
					otherwise reg	ulated:			
		ENTIFICATION							
Primary Entry Ro		alation				NF	PA/HMIS		
Target Organs:	N/A					HEALTH	1		
Acute Effects:	N/A					FLMMBLT	(. 1		
Inhalation: Sli	ight irritation of	respiratory tract.				REACTIVIT			
Eye: Du	ust may cause i	rritation or corneal i	njury.			PPE (Sec.8	S)		
Skin: Es	sentially non-iri	ritating to skin. Skin	absorption is unl	ikely due to physical	properties				
•	ral toxicity is bel	ieve to be low.							
Carcinogenicity:	N/A								
Medical Conditio		By Long-Term Ex	posure:	Accumulation of du	st in the respiratory syste	m			
may cause congestion. Chronic Effects: If these materials are used in a manner that could generate airborne particles (dust), it is recommended that									
omonic Enects.				0	to the American Confere				
		Hygienists (ACGIH)	0						
SECTION 4 FIR	RST AID MEA	SURES							
Inhalation: Re	emove to fresh	air and gargle with v	vater. Treat any i	rritation symptomatic	ally. Call a physician if co	ondition persist	S.		
Eye Contact: In	case of contact	immediately flush v	with plenty of low	pressure water for a	t least				
	15 minutes. Remove any contact lenses to ensure thorough flushing.								
	Wash well with soap and running water.								
Ingestion: No adverse effects anticipated by this route of exposure incidental to proper handling.									
	-		•	mmunity medical su	oport				
	-	nd symptoms persis	τ.						
Note to Physicians: N/A Special Precautions / Procedures: N/A									

		NG MEASURES					
Flash Point:	N/A						
Flash Point Meth							
Burning Rate:	N/A						
Auto Ignition Te	emperature:	Not Determined					
LEL: N	I∕A						
-	N/A						
Flammability Cla	assification:	1 Slight (HMIS, NFPA)					
Extinguishing M	ledia:	Water spray, dry chemical, foam, or carbon dioxide.					
Unusual Fire of Explosion Hazards: May form flammable dust-air mixture.							
Hazardous Com	bustion Pro	ducts: Carbon monoxide, carbon dioxide, nitrogen oxide and smoke.					
		Under certain conditions some aliphatic aldehydes and carboxylic acids					
		may form.					
Fire-Fighting Ins	structions:	Do not release runoff from fire controls methods to sewers or waterways.					
Avoid inhalation of fume or smoke.							
Fire-Fighting Eq	uipment:	Because fire may produce toxic thermal decomposition products, wear a					
		self-contained breathing apparatus (SCBA) with full facepiece operated					
		in pressure-demand or positive-pressure mode.					
SECTION 6 AC	CCIDENTA	L RELEASE MEASURES					
Spill / Leak Proc	cedures:	N/A					
Small Spills: S	Scoop into a d	container for disposal, suction up remaining material with a high efficiency					
-	'acuum clean						
Large Spills: S	Scoop into a d	container for disposal, suction up remaining material with a high efficiency					
Va	acuum clean	ier.					
Containment: F	or large spill	s, avoid suspending particles, collect for later disposal. Do not release					
in	nto sewers or	r waterways.					
Cleanup: N	lo special rec	quirements.					
Regulatory Requ		N/A					
SECTION 7 HA	ANDLING A	AND STORAGE					
Handling Precau	utions:	Keep containers closed at all times. Avoid creating dust. Keep away from ignition sources.					
Handling Precau Storage Require		Keep containers closed at all times. Avoid creating dust. Keep away from ignition sources. Store in a cool, dry location.					
-	ements:						
Storage Require Regulatory Requ	ements: uirement:	Store in a cool, dry location.					
Storage Require Regulatory Requ	ements: uirement: XPOSURE	Store in a cool, dry location. N/A					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor	ements: uirement: XPOSURE ntrols:	Store in a cool, dry location. N/A					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P	ements: uirement: XPOSURE ntrols: Provide gener	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P	ements: uirement: XPOSURE ntrols: Provide gener pelow OSHA	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P	ements: uirement: XPOSURE ntrols: Provide gener below OSHA dispersion into	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P	ements: uirement: XPOSURE ntrols: Provide gener below OSHA lispersion into Controls:	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P bi di Administrative C	ements: uirement: XPOSURE ntrols: Provide gener below OSHA lispersion into Controls: tection:	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant of the work area by controlling it at its source.					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P bi di Administrative C	ements: uirement: XPOSURE ntrols: Provide gener below OSHA dispersion into Controls: tection:	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant to the work area by controlling it at its source. Seek professional advise prior to respirator selection and use.					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P bi di Administrative C	ements: uirement: XPOSURE ntrols: Provide gener below OSHA dispersion into Controls: tection:	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant o the work area by controlling it at its source. Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P bi di Administrative C	ements: uirement: XPOSURE ntrols: Provide gener below OSHA lispersion into Controls: tection:	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant to the work area by controlling it at its source. Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P bi di Administrative C	ements: uirement: XPOSURE ntrols: Provide gener below OSHA lispersion into Controls: tection:	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant to the work area by controlling it at its source. Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P bi di Administrative C	ements: uirement: XPOSURE ntrols: Provide gener below OSHA lispersion into Controls: tection:	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant to the work area by controlling it at its source. Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P bi di Administrative C	ements: uirement: XPOSURE ntrols: Provide gener below OSHA lispersion into Controls: tection:	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant to the work area by controlling it at its source. Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operation (cleaning spills, reactor vessels, or storage tanks), wear					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P di Administrative C Respiratory Prot	ements: uirement: XPOSURE ntrols: Provide gener below OSHA lispersion into Controls: tection:	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant to the work area by controlling it at its source. Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operation (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. Warning! Air-purified respirators do not protect workers in oxygen-deficient					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P di Administrative C Respiratory Prot	ements: uirement: XPOSURE ntrols: Provide gener below OSHA lispersion into Controls: tection:	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant to the work area by controlling it at its source. Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operation (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. Warning! Air-purified respirators do not protect workers in oxygen-deficient atmospheres.					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P di Administrative C Respiratory Prot	ements: uirement: XPOSURE ntrols: Provide gener below OSHA lispersion into Controls: tection:	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant o the work area by controlling it at its source. Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operation (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. Warning! Air-purified respirators do not protect workers in oxygen-deficient atmospheres. ent: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P di Administrative C Respiratory Prot	ements: uirement: XPOSURE ntrols: Provide gener below OSHA lispersion into Controls: tection:	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant o the work area by controlling it at its source. Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operation (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. Warning! Air-purified respirators do not protect workers in oxygen-deficient atmospheres. ent: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P di Administrative C Respiratory Prot	ements: uirement: XPOSURE ntrols: Provide gener below OSHA lispersion into Controls: tection:	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant to the work area by controlling it at its source. Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operation (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. Warning! Air-purified respirators do not protect workers in oxygen-deficient atmospheres. ent: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye and face protection regulations					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P di Administrative C Respiratory Prot	ements: uirement: XPOSURE ntrols: Provide gener below OSHA lispersion into Controls: tection:	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant o the work area by controlling it at its source. Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operation (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. Warning! Air-purified respirators do not protect workers in oxygen-deficient atmospheres. ent: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protection regulations (29CFR 1910.133). Contact lenses are not eye protective devices. Appropriate					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P bi di Administrative C Respiratory Prot	ements: uirement: XPOSURE ntrols: Provide gener below OSHA lispersion into Controls: tection: hing/Equipm	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant to the work area by controlling it at its source. Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operation (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. Warning! Air-purified respirators do not protect workers in oxygen-deficient atmospheres. ent: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye and face protection regulations (29CFR 1910.133). Contact lenses are not eye protective devices. Appropriate protection must be worn instead of, or in conjunction with contact lenses.					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P bi di Administrative C Respiratory Prot	ements: uirement: XPOSURE ntrols: Provide gener below OSHA lispersion into Controls: tection: hing/Equipm	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant o the work area by controlling it at its source. Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operation (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. Warning! Air-purified respirators do not protect workers in oxygen-deficient atmospheres. ent: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye and face protection regulations (29CFR 1910.133). Contact lenses are not eye protective devices. Appropriate protection must be worn instead of, or in conjunction with contact lenses. emergency eyewash stations and washing facilities available in work area.					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P bi di Administrative C Respiratory Prot	ements: uirement: XPOSURE ntrols: Provide gener below OSHA lispersion into Controls: tection: hing/Equipment: Make e Equipment:	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant to the work area by controlling it at its source. Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operation (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. Warning! Air-purified respirators do not protect workers in oxygen-deficient atmospheres. ent: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye and face protection regulations (29CFR 1910.133). Contact lenses are not eye protective devices. Appropriate protection must be worn instead of, or in conjunction with contact lenses. emergency eyewash stations and washing facilities available in work area. Separate contaminated work clothing from street clothes. Launder before					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P bi di Administrative C Respiratory Prot	ements: uirement: XPOSURE ntrols: Provide gener below OSHA lispersion into Controls: tection: hing/Equipment: Make e Equipment:	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant to the work area by controlling it at its source. Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operation (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. Warning! Air-purified respirators do not protect workers in oxygen-deficient atmospheres. ent: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye and face protection regulations (29CFR 1910.133). Contact lenses are not eye protective devices. Appropriate protection must be worn instead of, or in conjunction with contact lenses. emergency eyewash stations and washing facilities available in work area. Separate contaminated work clothing from street clothes. Launder before re-use. Remove this material from your shoes and clean personal protective					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P bi di Administrative C Respiratory Prot	ements: uirement: XPOSURE ntrols: Provide gener below OSHA lispersion into Controls: tection: tection: ming/Equipment: Make e Equipment:	Store in a cool, dry location. N/A CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant o the work area by controlling it at its source. Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operation (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. Warning! Air-purified respirators do not protect workers in oxygen-deficient atmospheres. ent: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye and face protection regulations (29CFR 1910.133). Contact lenses are not eye protective devices. Appropriate protection must be worn instead of, or in conjunction with contact lenses. emergency eyewash stations and washing facilities available in work area. Separate contaminated work clothing from street clothes. Launder before re-use. Remove this material from your shoes and clean personal protective equipment.					
Storage Require Regulatory Requ SECTION 8 EX Engineering Cor Ventilation: P bi di Administrative C Respiratory Prot	ements: uirement: XPOSURE ntrols: Provide gener below OSHA lispersion into Controls: tection: tection: ming/Equipment: Make e Equipment:	Store in a cool, dry location. NA CONTROLS / PERSONAL PROTECTION ral or local exhaust ventilation systems to maintain airborne concentrations PELs (sec.2). Local exhaust ventilation is preferred because it prevents contaminant o the work area by controlling it at its source. Seek professional advise prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operation (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. Warning! Air-purified respirators do not protect workers in oxygen-deficient atmospheres. ent: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye and face protection regulations (29CFR 1910.133). Contact lenses are not eye protective devices. Appropriate protection must be worn instead of, or in conjunction with contact lenses. semergency eyewash stations and washing facilities available in work area. Separate contaminated work clothing from street clothes. Launder before re-use. Remove this material from your shoes and clean personal protective equipment. nk, or smoke in works areas. Practice good personal hygiene after using this					

SECTION 9 PHYSIC	AL AND CHEMICAL PROPERTIES									
Physical State:		Water Solubility:	Insoluble							
Appearance and Odor:	Black, free flowing powder, odorless	Other Solubilities:	N/A							
Odor Threshold:	N/A	Boiling Point:	N/A							
Vapor Pressure:	N/A	Melting Point:	Approx. 150 C							
Vapor Density (Air=1):	Heavier than air.	Viscosity:	N/A							
Formula Weight:	N/A	Refractive Index:	N/A							
Relative Density:	1.0 - 1.2	Surface Tension:	N/A							
Specific Gravity:	$(H_2O)=1$, at 4°C): 1.2	% Volatile:	N/A							
pH:	N/A	Evaporation Rate:	N/A							
pri.		Decomposition Temp:	>200C							
SECTION 10 STABIL	ITY AND REACTIVITY									
Stability: Stable Pr	roduct									
Polymerization: N/	/Α									
Chemical Incompatibili	ties: N/A									
Conditions to Avoid: N/	/Α									
Hazardous Decomposition Products: May include nitrogen and carbon oxides										
SECTION 11 TOXICO	DLOGICAL INFORMATION									
Eye Effe	cts: N/A	Toxicity Data:*								
Skin Effe	ects: N/A	Acute Inhalation Effects:	N/A							
		Acute Oral Effects:	N/A							
		Chronic Effects:	N/A							
			N/A							
		Carcinogenicity:	IV/A							
		Mutagenicity: Ames Test	(Estimated from the results of							
		Negative	testing the constituent components)							
		Teratogenicity:	N/A							
	· · · · · · · · · · · · · · · · · · ·									
"See NIUSH, RTECS	for additional toxicity data.									
	GICAL INFORMATION									
Ecotoxicity: N/	Ά									
Environmental Fate:	N/A									
Environmental Degrada	ation: N/A									
Soil Absorption / Mobili	ity: N/A									
	SAL CONSIDERATIONS aterial may be incinerated / or recycled for	its Iron Oxide under conditions :	which meet							
	Il, state, and local environmental regulation		which meet							
	-									
Disposal Regulatory Re										
Container Cleaning and	I Disposal: N/A									
SECTION 14 TRANS	PORT INFORMATION									
DOT Transportation Da	ta (49 CFR 172.101): Not specifically	listed.								
Shipping Name: N/	A Packaging Authorization	IS	Quantity Limitations							
Shipping Symbol: N/	A a) Exceptions:	N/A	a) Passenger, Aircraft, or							
Hazard Class: N/		N/A	Railcar: N/A							
ID No: N/		N/A								
Packing Group: N/	, 00		Vessel Stowage Requirements							
Label: N/			a) Vessel Stowage: N/A							
			-							
Special Provisions: N/	~		b) Other: N/A							

SECTION 15 REGULATORY INFORMATION

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33) RCRA Hazardous Waste Classification: (40 CFR 261): Not classified CERCLA Hazardous Substance (40 CFR 302.4) listed unlisted specific per RCRA, sec. 3001; CWA sec.311 (b)(4); CWA, Sec. 307(a),CAA,Sec.112 CERCLA Reportable Quantity(RQ), Not listed SARA 311/312 Codes: N/A

SARA Toxic Chemical (40 CFR 372.65): Not listed

SARA EHS (Extremely Hazardous Substance) (40CFR 355): Not listed, Threshold Planning Quantity (TPQ)

OSHA Regulations:

Air Containment (29 CFR 1910.1000< Table Z-1-A): Particulates not otherwise regulated. **State Regulations:** Check your states regulations that may specifically list copy machine toner.

SECTION 16 OTHER INFORMATION

Prepared By: N/A Revision Notes: N/A Additional Hazard Rating System: N/A

> THIS INFORMATION IN THIS MSDS WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY EXPRESS OR IMPLIED, REGARDLESS IT'S CORRECTNESS. THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL, AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.